Serial No. 10/502,309

Amendments to the Claims

- (Currently amended) Method A method of securing messages 1. exchanged over a data transmission network between a server (1) and a small client (2), the small client comprising a smart card or a mobile communication system, wherein the small client [[that]] does not have the resources necessary for providing security functions, the method being performed under the control of an authority that defines message exchange rules, the method comprising providing wherein control is provided in a decentralized manner by a representative (3) of the authority, and setting up communication between the client and the server only via the representative of the authority, wherein the representative of the <u>authority is</u> inserted permanently into the network in the vicinity of the client (2) and between the server (1) and the client (2) during the secure exchange of messages, and wherein the representative of the authority translates to translate transmitted messages transmitted between the server and the client and $t\phi$ $d\phi dy$ applies verifications decided on by the authority to <u>said</u> transmitted messages.
- 2. (Currently amended) Méthod The method according to claim 1, further comprising using wherein a first protocol (P) is used for exchanges between the server (1) and the representative (3) of the authority, and using a second protocol (P') different from the first protocol (P) is used for exchanges between the representative (3) of the authority and the client (2).

3. (Currently amended) Méthød <u>The method</u> according to claim 1, wherein/ for the exchange of messages/ <u>further comprising:</u>

setting up a first secure channel (4) 18 \pm 62 up between the server (1) and the representative (3) of the authority, using a first key (Ks) known to the representative (3) of the authority and to the server (1) but not to the client (2), and using a first encryption algorithm (AL), and

setting up a second secure channel (5) 18 86% up between the representative (3) of the authority and the client (2), using a second key (Kc) known to the representative (3) of the authority and to the client (2) but not to the server (1), and using a second encryption algorithm (AL').

4. (Currently amended) Device a device comprising for securing messades exchanged over a data transmission network between a server (1) and a small client (2) that does not have the resources necessary for providing [[the]] a security function, the small client comprising a smart card or a mobile communication system, the small client being under the control of an authority that defines message exchange rules, the device also comprising means for securing messages exchanged over a data transmission network between the server and the small client, the securing means comprising a decentralized control device or representative (3) of the authority, the representative of the authority being inserted permanently into the network in the vicinity of the client (2) and between the server (1) and the client (2) during the secure exchange of messages, to set up communication between the client and the server only via the representative of the authority, to translate translate translate authority transmitted between the server and the client, and to apply verifications

decided on by the authority to <u>said</u> transmitted messages.

- 5. (Currently amended) Dévité The device according to claim 4, wherein the decentralized control device or representative (3) of the authority is a data processing microsystem secured by hardware, inserted permanently between the server (1) and the client (2) during the exchange of messages.
- 6. (Currently amended) Device The device according to claim 5, wherein:

the server (1) is a data processing system comprising an input-output port (1a);

the client (2) is a data processing microsystem comprising an inputoutput port (12);

the representative (3) of the authority is a data processing microsystem secured by hardware and comprising an interface device (13):

a dedicated interface system (7) is provided, comprising an inputoutput port (8) connected to the input-output port (1a) of the server data
processing system (1), comprising a card port (9) connected to the inputoutput port (12) of the client data processing microsystem (2), comprising
an input-output port (10) connected to the interface device (13) of the
representative (3) of the authority data processing microsystem, and
comprising a controller (11) programmed to control communication between
the input-output ports (8), (9) and (10);

the controller (11) and the representative (3) of the authority are programmed so that:

the server data processing system (1) sends a request A to the client

data processing microsystem (2), and that request is received by the controller (11);

the controller (11) transmits the request A to the representative (3) of the authority, which sends it back a response Ra;

the controller (11) uses that response Ra to calculate a request A' that is sent to the client data processing microsystem (2);

the client data processing microsystem (2) processes the request A' to prepare a response B';

the client data processing microsystem (2) sends the response B' to the server data processing system (1); that response is received by the controller (11);

the controller (11) transmits the response B' to the representative (3) of the authority, which sends it back a response Rb;

the controller (11) uses that response Rb to calculate a response B that is sent to the server data processing system (1).

7. (Currently amended) ������ The device according to claim 6, wherein:

the client (2) is a first smart card;

the representative (3) of the authority is a second smart card;

the dedicated interface system is a smart card reader (7) comprising two card ports (9) and (10).

8. (Currently amended) **Dévice** The device according to claim 6, wherein:

the client (2) is a mobile communication system;

the server (1) is a data processing system communicating with the client (2) via a physical connection or via a wireless communication

network:

the representative (3) of the authority is a smart card representing the operator of the wireless communication network (known as the SIM card in telephones conforming to the GSM standard).

9. (Currently amended) Device The device according to claim 6, wherein:

the client (2) is a smart card;

the representative (3) of the authority is a data processing system secured by hardware;

the dedicated interface system (7) is a machine comprising a card port (9) and a dedicated input-output interface (10) for connection to the representative (3) of the authority data processing system.